

## TECHNICAL DATA

Description	FP 53	FP 115	FP 240	FP 400	FP 720
<b>Dimensions of the container without applied parts and fittings</b>					
Net width (mm)	635	835	1035	1235	1235
Net height (mm)	620	705	825	1025	1530
Net depth (mm)	575	645	745	765	865
<b>Internal dimensions</b>					
Width (mm)	400	600	800	1000	1000
Height (mm)	400	480	600	800	1200
Depth (mm)	340	410	510	510	610
<b>Measurements</b>					
Internal volume (l)	53	115	240	400	720
Net weight device (empty)	44	62	96	145	194
Maximum total load capacity (kg)	40	50	70	90	120
Maximum capacity per rack (kg)	15	20	30	35	45
<b>Temperature technical data</b>					
Temperature range 5 °C above room temperature up to ( °C )	300	300	300	300	300
Temperature variation at 150 °C	2	1,8	2	2,5	2
Temperature fluctuation over time at 150 °C	0,3	0,3	0,3	0,3	0,3
Warm- up time at 150 °C (min)	24	30	27	35	39
Recovery time after 30 s of opening the door at 150 °C	5	8	10	17	20
<b>Electrical data</b>					
Nominal power (version 120v) [kW]	1,2	1,6	-	-	-
Nominal power (version 208v) [kW]	-	-	2,7	3,4	5
Nominal power (version 230v) [kW]	1,2	1,6	2,7	-	-
Nominal power (version 400v) [kW]	-	-	-	3,4	5
<b>Internal structures</b>					
Number of shelves (standard/max)	2/5	2/6	2/7	2/10	2/16